

VBA100-30

10kHz - 100MHz 30W Amplifier

- Rugged Silicon DMOS technology
- Class A for maximum mismatch drive
- General linear power requirements


The **VBA100-30** is a member of our family of 10 kHz-100 MHz high power amplifiers, designed primarily for EMC applications.

The VBA100 series is based on rugged silicon DMOS technology. The amplifier operates in class A, the benefits for EMC applications being very low distortion and tolerance of 100% mismatch.



Fold-back protection is neither fitted nor needed! This makes it supremely suited for very demanding transducer requirements.

Performance Chart



Choose **Vectawave** for high efficiency and performance in your regular power amplifier requirements.

See overleaf for technical specification

Specifications

VBA100-30

Electrical

Frequency Range (Instantaneous)	0.01-100MHz
Rated Output Power	30W Min (40W typical)
Output Power at 1dB Gain Compression	25W Min (35W typical)
Gain	46dB Min
Third Order Intercept Point (see note 1)	54dBm
Gain variation with Frequency	±2dB
Harmonics at 25W Output Power	Better than -20dBc
Output Impedance	50 Ohms
Stability	Unconditional
Output VSWR Tolerance (see note 2)	Infinity:1
Input VSWR	2:1 (Max)
Supply Voltage	85-264V ac
Supply Frequency Range	47-63Hz
Supply Power	<120VA (Max)
Mains Connector	IEC320

Mechanical

RF Connector Style	Type N Female
Safety Interlock	2 x BNC, S/C and O/C to Mute
USB/GPIB Interface	Optional
Dimensions	19 inch, 3U Case, 400mm Deep
Mass	12kg
Operating Temperature Range	0-40°C
Case Style Options	Rack mount with Front or Rear panel connectors Bench mount with Front panel connectors

Regulatory Compliance

Conducted and Radiated Emissions	EN61326 Class A
Conducted and Radiated Immunity	EN61326:1997 Table 1
Safety	EN61010-1

Notes

- 1 The third order intercept point is a nominal value, as its calculation depends upon the power level at which distortion measurements are made.
- 2 Output VSWR tolerance is specified for excitation within the permitted levels and frequency range.



Represented Worldwide

Vectawave Technology Ltd.
Unit D, The Apex,
St Cross Business Park, Monks Brook,
Newport, Isle of Wight, PO30 5XW

Tel: +44 (0) 1983 821 818

E-mail: sales@vectawave.co.uk